

Global Consulting Inc.

"Managing projects to success"

BUTTWELD FITTINGS



BUTTWELD FITTINGS



A.) Type Range

ELBOW 90° LR & SR, ELBOW 45° LR & SR, ELBOW 180° LR & SR, EQUAL TEE / RED - TEE CON - RED / ECC - RED, STUB END TYPE A & B CROSS / RED CROSS, CAP / SS WELDDOLET

B.) Materials

Steel grade 304, 304H, 304L, 316L, 321, 321H, 347H, 317L, 904L etc.

Duplex steel S32205, S32750, S31803 etc.


C.) Thickness: SCH5 / 10S / 40 / 40S / 80 / 80S/ STD / XS / XSS / 160

D.) Size: Seamless: 1/2" (21.3mm) to 24" (610 mm)

Welded: 1/2" (21.3mm) to 64" (1620mm)

E.) Standard: ASME B16.9 / B16.28 / B16.5-2016, EN 10253-3 / -4

WELDOLETS



NW	COLLECTOR	3000 Lbs.			6000 Lbs.		
		A mm	B mm	Kg.	A mm	B mm	Kg.
1/2"	1/2"-36"	19	33	0.085	28.5	35	0.18
3/4"	3/4"-36"	22	43	0.17	32	43	0.45
1"	1"-36"	28.5	52	0.35	38	51	0.75
1 1/4"	1 1/4"-36"	33	64	0.50	44.5	64	0.95
1 1/2"	1 1/2"-36"	33	72	0.62	51	70	1.15
2"	2"-36"	38	88	0.90	56	83	1.85
2 1/2"	2 1/2"-36"	41	105	1.70			
3"	3"-36"	44.5	122	1.95			
4"	4"-36"	51	152	3.65			



Kspm Global Consulting Inc.

Head Office:

1113 Kestell Blvd., Oakville, Ontario L6H 7M6 Canada.

Website: www.kspmglobal.ca E-mail: Operations@kspmglobal.ca